



## NKHDMI-\*

The HDMI 2.0 patch cables with overmolded flex relief and rugged metal cable carrier fit and lock with NAHDMI-W-\*.

\* The cables are available in 0.6 m, 1 m, 3 m, 5 m and 10 m (10 m cable complies with HDMI 1.4 specifications) cable length.

Neutrik's HDMI solution for the transmission of any digital TV and PC video format including high-definition video (HDTV) can be integrated in networks very easy.

### Features & Benefits

- HDMI 2.0 - data rate up to 18 GBit/s
- Dust and water resistant acc. to IP65 safety standard in combination with NAHDMI-W\*
- Push Pull mating design provides secure locking system if mated with NAHDMI-W\*
- Shielded connection - high noise immunity and EMI protection
- Removable rugged diecast cable carrier
- Mates with conventional HDMI receptacles if cable carrier is removed

## Technical Information

Product	
Title	NKHDMI-*

Mechanical	
Wiresize	
Minimum bending radius allowed	40 mm
Lifetime	> 1000 mating cycles

Material	
Contact plating	Au
Contacts	Brass (CuZn39Pb3)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel

Environmental	
Flammability	UL 94 V-0
Standard compliance	HDMI 2.0 specifications for length up to 3 m incl. HDMI 1.4 specifications for length > 3 m
Temperature range	-25 °C to +85 °C