


1800B Paired - Single-Pair Cable

  	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

24 AWG stranded (7x32) tinned copper conductors, Datalene® insulation, twisted pairs, overall Beldfoil® shield (100% coverage), 24 AWG drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	24
Stranding	7x32
Conductor Diameter	.024 in.
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material Trade Name	Datalene®
Insulation Material	FHDPE - Foam High Density Polyethylene
Insulation Diameter	.068 in.

Pair Color Code Chart :

Number	Color
1	Red & Black

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	24
Outer Shield Drain Wire Stranding	7x32
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

1800B Paired - Single-Pair Cable

Overall Nominal Diameter	.177 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +60°C
UL Temperature Rating	60°C
Bulk Cable Weight	18.3 lbs/1000 ft.
Max. Recommended Pulling Tension	16.5 lbs.
Min. Bend Radius (Install)	1.75 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMG
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
Other Specification	AES/EBU

FLAME TEST:

C(UL) Flame Test	FT4
------------------	-----

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	1801B

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	110 Ohms
Nom. Inductance	.18 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	12 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	26 pF/ft
Nominal Velocity of Propagation	76 %
Nom. Conductor DC Resistance @ 20 Deg. C	23.7 Ohms/1000 ft
Nom. Attenuation (dB/100 ft) :	

1800B Paired - Single-Pair Cable

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	.384			.69
	.7056			.93
	.768			.96
	1.024			1.07
	1.4112			1.19
	1.536			1.21
	2.048			1.31
	2.8224			1.41
	3.072			1.45
	4.096			1.57
	5.6448			1.76
	6.144			1.83
	8.192			2.01
	11.2896			2.24
	12.288			2.30
	24.576			3.08

Max. Operating Voltage - UL 300 V RMS

Max. Recommended Current 2.75 Amps per conductor @ 25°C

NOTES:

Notes For cross-connect use with 1803F (et al.) Digital Audio Snake Cables. The jacket and shield are bonded so both can be removed with automatic stripping equipment.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1800B 0071000	#24 FHDPE FS PR PVC	1000	16	VIOLET	C
1800B 0075000	#24 FHDPE FS PR PVC	5000	90	VIOLET	C
1800B 007U1000	#24 FHDPE FS PR PVC	U1000	17	VIOLET	
1800B T5X1000	#24 FHDPE FS PR PVC	1000	16	GRAY T5X	C
1800B T5X500	#24 FHDPE FS PR PVC	500	8	GRAY T5X	C
1800B T5XU1000	#24 FHDPE FS PR PVC	U1000	17	GRAY T5X	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 08-16-2005

1800B Paired - Single-Pair Cable

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.